

General Specifications

Exterior Lights

Component	Type
Headlamp	Oval, aligned by adjusting the reflector

Headlamp Alignment

Component	Dimension X
Headlamps	$X = 12 \text{ cm}/10 \text{ m} = 0^\circ$, 41 minutes = 1,2 %
Fog Lamps	$X = 22 \text{ cm}/10 \text{ m} = 1^\circ$, 16 minutes = 2,2 %

Bulb Chart – 12V

Lamp	Type	Wattage
Halogen headlamps (main beam)	H1	55
Halogen headlamps (dipped beam)	H1	55
Halogen fog lamps	H1	55
Side lamps	Push fit	5
Front indicators	Bayonet	21
Rear indicators	Bayonet	21
Side indicators	Bayonet	5
Brake lamps	Bayonet	21
Rear lamps	Bayonet	5
Reverse lamps	Bayonet	21
Rear fog lamps	Bayonet	21
License plate lamp	Push fit	5
Auxiliary brake lamp	Push fit	5

Lubricants, Adhesives and Sealers

	Ford Specification
Grease (for wiper linkage bearing/pivot shaft bearing bush)	SAM-1C-9111-A

Capacities

Reservoir	Litres
Windscreen and rear window without headlamp washers	4,0
Windscreen and rear window with headlamp washers	11,0

Washers

	Pump type
Windscreen and rear window	Electric pump
Headlamps	High-pressure pump fitted to washer reservoir

Angle between wiper arms and windscreen/rear window

Description	Angle
Windscreen	3°
Rear window (Estate)	4°

Windscreen Wipers

Windscreen wiper motor	Type
Windscreen	Electric, three-speed, self-parking Intermittent wipe control
Rear window	Electric, one-speed, self-parking

Torques

	Nm	lbf.ft
Headlamp screws	6	4
Fog lamp screws	4	3
Rear lamp assembly nuts	4	3
Middle rear lamp unit nuts	4	3
Auxiliary brake lamp screw	6	4
Windscreen wiper arm nut	20	15
Mounting plate bolts to windscreen wiper motor	12	9
Bolts – windscreen wiper motor with linkage to bulkhead	8	6
Wiper lever nut to windscreen wiper motor	24	18
Rear wiper arm nut	16	12
Mounting plate bolts to rear wiper motor	7	5
Bolts securing rear mounting plate to tailgate	7	5
Bolts of windscreen and rear window washer reservoir	3	2